

SOKKIA

DT220·DT520 DT520A·DT620

Electronic Digital Theodolites

SOKKIA's Breakthrough Technology Delivers Astonishing Operating Time – 220* Hours!

Featuring cutting-edge power-saving technology, an advanced angle measurement system and industry-leading dust & water protection, the SOKKIA Digital Theodolites offer unprecedented reliability and versatility in construction and engineering applications.

* DT620 model



DT220 • DT520 • DT520A • DT620

Electronic Digital Theodolites

The World's Longest Operating Time

- SOKKIA's innovative technology achieves the world's longest operating time* – 220 hours with the 7"-DT620 model.
- The DT520A operates up to 200 hours - the longest among 5" models*.
- At 7 hours/day, the DT620/DT520A can operate for more than 31/28 respective days without changing batteries.

* As of January 1, 2009

Advanced Angle Measurement System

- The DT series theodolites are equipped with market-proven absolute encoders. Advanced coding and digital processing technologies provide long-term reliability in any work-site conditions.
- 2"-DT220 incorporates IACS (Independent Angle Calibration System) to further enhance measurement reliability.
- 5"-DT520A and 7"-DT620 employ newly developed IACS-SD* technology that provides high accuracy with the power-efficient single-detection system.

* IACS with Single Detection



Quick, User-friendly Operation

- Start measurement as soon as you turn on the power without the need for 0-indexing.
- Easy-to-read LCD display has 20% larger digits than former models.
- The MENU key facilitates all instrument settings including angle units, resolutions, measurement modes, tilt compensation and so on.



Dual-axis Compensation (DT220 • DT520)

- DT220/DT520 models automatically compensate both Vertical and Horizontal angles by monitoring instrument tilt in X & Y directions.

Right-angle Beeps

- Beeps at each of the four right-angle directions to assist squaring.

Industry's Highest Dust- and Water-Protection

- All models comply with the rigorous IP66 standard, offering superior protection against powder-type dust and sudden showers.

* Among existing electronic theodolites, as of January 1, 2009

RS-232C Port

- Measurement data can be output to external devices via RS-232C data port*.

* Except DT620 model

Product names mentioned in this brochure are trademarks of their respective owners.
Designs and specifications are subject to change without notice.
Product colors in this brochure may vary slightly from those of the actual products owing to limitations of the printing process.

SOKKIA B.V. Head Office Europe, Russia & other CIS countries Phone +31-(0)36-5496000 www.sokkia.net

Specifications

	DT220	DT520	DT520A	DT620
Telescope				
Length	165 mm (6.5 in.)		160 mm (6.3 in.)	
Objective aperture	45 mm (1.8 in.)		35 mm (1.4 in.)	
Magnification	30 x		26 x	
Image	Erect			
Resolving power	3"		3.5"	
Field of view	1°30' (26 m/1,000 m)			
Minimum focus	0.9 m (3.0 ft.) from telescope center			
Stadia	Multiplication constant: 100, Additive constant: 0			
Reticle illumination	Built-in. Bright / Dim, selectable		—	
Angle measurement	Absolute rotary encoder scanning			
Display unit	Degree / Gon / Mil, selectable			
Display resolutions (selectable)	1" / 5", 0.2 / 1 mgon, 0.005 / 0.02 mil		5" / 10" 1 / 2 mgon 0.02 / 0.05 mil	
Accuracy (ISO 17123-3:2001)	2" / 0.6 mgon 0.01 mil	5" / 1.5 mgon / 0.025 mil		7" / 2.2 mgon 0.035 mil
Measuring mode	H	Clockwise, Counterclockwise, selectable. Hold, 0-set, available		
	V	Zenith 0 / Horizontal 0 / Horizontal 0±, Slope in %/‰, selectable		
Automatic dual-axis compensator	Dual-axis liquid tilt sensor Working range ±3'(±55mgon)		—	
General				
Display	LCD, 8 digits x 2 lines with backlight			
Keyboard	6 keys			
Control panel location	On both faces		On single face	
Interface	RS-232C, baud rate 1,200 bps		—	
Right-angle beeps	Provided			
Sensitivity of levels	Plate level	30"/2 mm	40"/2 mm	60"/2 mm
	Circular level	10"/2 mm		
Optical plummet	Image: Erect, Magnification: 3 x, Minimum focus: 0.3 m (1 ft.)			
Tribrach	Detachable		Fixed	
Operating temperature	-20 to +50°C (-4 to +122°F)			
Dust and water protection	IP66 (IEC 60529:2001)			
Instrument height	236 mm (9.3 in.) from tribrach bottom			
Size with handle	W165 x D165 x H341 mm (W6.5 x D6.5 x H13.4 in.)			
Weight with handle	4.4 kg (9.6 lb.)	4.3 kg (9.5 lb.)	4.2 kg (9.3 lb.)	3.9 kg (8.6 lb.)
Power supply				
Battery	LR14(C) batteries x 2			
Operating time w/alkaline batteries at 25°C (77°F)	Approx. 130 hours		Approx. 200 hours	Approx. 220 hours
Automatic power cut off	5/10/15/30 minutes after operation / none, selectable			

Standard accessories

- LR14(C) alkaline batteries (x2) • Lens cap • Lens hood • Plumb bob • Tool kit
- Operator's manual • Carrying case • Shoulder strap

Optional accessories:

- CP7 Tubular compass
- DE25 Diagonal eyepiece
- EL6 30x eyepiece for DT620
- ACE5 Auto-collimation eyepiece
- LAP1 Laser plummet module
- LSE1 Laser sighting eyepiece
- OF1 Solar filter